



創唯實業有限公司

PLASTRONIC TECHNOLOGY CO., LTD.

TEL : 886-2-2276-3375

www.loadcell.com.tw

E-mail: plastronictech@gmail.com


FAX : 886-2-2276-3557

www.plastronic.com.tw

新北市24252新莊區化成路398巷13號

No.13, Lane 398, Hua-Cheng Rd., Sin-Jhuang District, New Taipei City 24252, Taiwan

## PF6



主要外形尺寸  
Main Dimensions and Accessories

量程 Capacity	尺寸 Size mm											
kg	A	B	C	D	E	F	G	K	M	N	J	S
100-750	173.0	43.0	63.0	65.0	20.0	7.25	19.0	120.5	M8	30.0	45	7.5

應用：平台秤、料斗秤

Applications : Platform Scale, hopper scale

### 技術規格 Specification

額定荷重 Rated Capacities	150~1000 (kg)
額定輸出 Rated Output	2.0 mV/V±0.25%
精度等級 Accuracy class	
非線性 Non-linearity	0.03 %F.S
遲滯 Hysteresis	0.03 %F.S
重複性 Repeatability	0.02 %F.S
蠕變/回零(20分鐘) 20mins Creep/DR	0.03 %F.S
輸出溫度影響 Temperature Effect On Output	0.02 %F.S/10°C
零點溫度影響 Temperature Effect On Zero	0.03 %F.S/10°C
零點平衡 Zero Balance	±0.0200 mV/V
輸入阻抗 Input Impedance	390±15 Ω
輸出阻抗 Output Impedance	350±5 Ω
絕緣阻抗 Insulation Impedance	≥5000 MΩ
安全過載率 Safe Overload	150 %F.S
極限過載率 Ultimate Overload	200 %F.S
工作溫度範圍 Operating Temperature Range	-20~60 °C
建議工作電壓 Recommended Excitation	5~12 VDC
最大工作電壓 Maximum Excitation	15 VDC
材質 Construction	鋼合金 Alloy Steel
防水等級 Protection Class	IP68(焊封)
電纜線 Cable	φ5.4×6 m
建議台面尺寸 Recommended Platform Size	

接線方式 Mode of Connection

紅：電源+，黑：電源-，綠：信號+，白：信號-  
Red (EXC+) ,Black (EXC-) ,Green (SIG+) ,White (SIG-)